

RED Extreme Pressure Non-Melt Grease

Excellent Extreme Pressure Grease, Particularly where Bearings and Chassis Points are Subject to Wet or High Temperature Conditions or Heavy Loads.

- Excellent shear stability
- High temperature protection up to 500°F
- Excellent load carrying capacity – 65 Timken load
- Extreme pressure protection
- Resistant to oxidation, acids, water, salt spray, weather, dirt, dust and steam
- Contains special corrosion and rust inhibitors
- Exceptional anti-wear properties, even at high temperatures
- Excellent adhesive and cohesive properties

Net Wt. 14 OZ. (396 Grams)

CAUTION:

Do not take internally.

May be harmful if swallowed. For eye contact, flush with plenty of water until irritation subsides. For skin contact, wash with soap and water.

KEEP OUT REACH OF CHILDREN.

Directions Place This End In Gun First

On first application, force sufficient grease through the bearing or fitting to flush out all the old grease and contaminants.

Where possible, wash out all old grease entirely, and replace with RED GREASE for maximum protection.



UNITED RESEARCH CORP
PHONE 800.506.4414
www.unitedresearchcorp.com

GENERAL SPECIFICATIONS:

NLGI GRADE	2
Dropping Point	500°F
Timken Load	65
Corrosion Resistance	Excellent
Color	Dark Red

