

SURE-FOOT

SLIP RESISTANT

TEXTURED

EPOXY COATING

• EASY TO USE

• DRIES QUICKLY

CONTAINS NO CFC'S WHICH
DEPLETE THE OZONE LAYER

Adheres to Fiberglass, Wood, Steel,
Concrete and Most other surfaces.

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR
VAPORS MAY CAUSE FLASH FIRE • VAPOR HARMFUL
CAUSES EYE IRRITATION • CONTENTS UNDER PRESSURE
SEE OTHER CAUTIONS ON BACK PANEL

NET WT.
12 OZ.
(340 Grams)

OVERCAP INDICATES COLOR

A slip-resistant, epoxy coating that cures to a hard, flat, textured finish. Designed for interior and exterior use on concrete, steel, wood, fiberglass, aluminum and other surfaces where a slip-resistant finish is desired.

EFFECTIVE ON: Steps, ramps, loading docks, ladders, running boards, showers, bathtubs, around machinery or anywhere water or other slippery conditions exist.

SURFACE PREPARATION: The surface should be dry, clean and free of oil, wax, dirt, loose paint and/or other contaminants. Previously painted surfaces should be cleaned with a mild cleaner, rinsed and dried. Before initial application to surface, a light etch or sanding is recommended. **WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Test a small area for compatibility and adhesion. The coating is self-priming on most surfaces.

DRY TIME: Dries to touch in approximately one hour. Make sure first coat is dry before applying second coat. The rate of cure will vary with the film thickness, temperature and humidity. Wait 24 hours before subjecting to heavy foot traffic. Application will continue to cure for several days. Recoat every 3 to 6 months depending on wear.

USE DIRECTIONS: For best results apply with ambient temperatures between 60°F to 90°F. Shake can until ball rattles freely and then for an additional 60 seconds. Epoxy must be mixed well before and during use to achieve the correct color and texture. For best results shake can periodically during use. Spray in a sweeping motion at a distance of 12 to 15 inches from area to be treated. **IMPORTANT:** To prevent dogging; after each use, invert can and spray a few short bursts to clear valve.

DANGER: Contains Acetone (67-64-1), Epoxy Resin (Proprietary), Propane (74-98-6), Xylene (1330-20-7), Toluene (108-88-3), Butane (106-97-8), Ethyl Benzene (100-41-4), VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES SKIN, NOSE AND THROAT IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARMFUL IF ABSORBED THROUGH THE SKIN. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F.

NOTICE: Repeated and prolonged exposure to solvents may cause permanent brain and nervous system damage. May cause liver and kidney damage. In addition, inhaling the concentrated contents is harmful and may be fatal.

Vapor may ignite explosively. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

Use only with adequate ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Failure to wear proper respiratory protection may result in permanent brain and nervous system damage. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention. EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration or administer oxygen. IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

KEEP OUT OF REACH OF CHILDREN

HMIS RATINGS: Health, 2; Flammability, 4; Reactivity, 0; Personal Protection, 1.

SLIP RESISTANT COATINGS 80% VOC

For further information consult Material Safety Data Sheet.

24 HOUR MEDICAL / TRANSPORTATION EMERGENCY 1-800-255-3924

URC UNITED RESEARCH CORP
PHONE: 800.506.6416
www.unitedresearchcorp.com

